

## APM AC300 Plastic Paint (Metallic Colors)

### ASIA PAINT SINGAPORE

Chemwatch: 5175-75  
Version No: 2.1.1.1  
Safety Data Sheet

Chemwatch Hazard Alert Code: 3

Issue Date: 18/05/2015  
Print Date: 17/09/2015  
Initial Date: **Not Available**  
S.GHS.SGP.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                                      |  |
|--------------------------------------|--|
| <b>Product name</b>                  | APM AC300 Plastic Paint (Metallic Colors)  |
| <b>Synonyms</b>                      | Not Available  |
| <b>Proper shipping name</b>          | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| <b>Other means of identification</b> | Not Available  |

### Relevant identified uses of the substance or mixture and uses advised against

|                                 |  |
|---------------------------------|--|
| <b>Relevant identified uses</b> | Air drying type modified acrylic resin based coating for the decoration and protection of plastic substrates such as ABS, PS, PC and HIPS. |
|---------------------------------|--|

### Details of the supplier of the safety data sheet

|                                |                                |
|--------------------------------|--------------------------------|
| <b>Registered company name</b> | ASIA PAINT SINGAPORE           |
| <b>Address</b>                 | 20 Tuas Ave 8 639235 Singapore |
| <b>Telephone</b>               | +65 65 463 955                 |
| <b>Fax</b>                     | +65 65 463 855                 |
| <b>Website</b>                 | www.asiapaintsingapore.com     |
| <b>Email</b>                   | sales@asiapaintsingapore.com   |

### Emergency telephone number

|  |               |
|--|---------------|
| <b>Association / Organisation</b>        | Not Available |
| <b>Emergency telephone numbers</b>       | Not Available |
| <b>Other emergency telephone numbers</b> | Not Available |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

#### CHEMWATCH HAZARD RATINGS

|              | Min | Max |
|--------------|-----|-----|
| Flammability | 3   | 4   |
| Toxicity     | 1   | 2   |
| Body Contact | 2   | 3   |
| Reactivity   | 1   | 2   |
| Chronic      | 3   | 4   |

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

|                           |   |
|---------------------------|---|
| <b>GHS Classification</b> | Flammable Liquid Category 2, Eye Irritation Category 2, Reproductive Toxicity Category 1B, STOT - SE (Narcosis) Category 3, Chronic Aquatic Hazard Category 2 |
|---------------------------|---|

### Label elements

|                           |   |
|---------------------------|---|
| <b>GHS label elements</b> |  |
|---------------------------|---|

|                    |               |
|--------------------|---------------|
| <b>SIGNAL WORD</b> | <b>DANGER</b> |
|--------------------|---------------|

### Hazard statement(s)

|             |                                    |
|-------------|------------------------------------|
| <b>H225</b> | Highly flammable liquid and vapour |
| <b>H319</b> | Causes serious eye irritation      |

|      |   |
|------|---|
| H360 | May damage fertility or the unborn child        |
| H336 | May cause drowsiness or dizziness               |
| H411 | Toxic to aquatic life with long lasting effects |

**Precautionary statement(s) Prevention**

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.                     |
| P240 | Ground/bond container and receiving equipment.   |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.              |
| P242 | Use only non-sparking tools.   |
| P243 | Take precautionary measures against static discharge.  |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P273 | Avoid release to the environment.  |

**Precautionary statement(s) Response**

|                |  |
|----------------|--|
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P370+P378      | In case of fire: Use alcohol resistant foam or normal protein foam for extinction.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.  |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P391           | Collect spillage.  |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |

**Precautionary statement(s) Storage**

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool.                     |
| P405      | Store locked up.   |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

**Precautionary statement(s) Disposal**

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration |
|------|--|

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No    | %[weight] | Name                                   |
|-----------|-----------|--|
| 123-86-4  | 10-30     | <u>n-butyl acetate</u>                 |
| 141-78-6  | <10       | <u>ethyl acetate</u>                   |
| 7429-90-5 | <10       | <u>aluminium flake</u>                 |
| 84-74-2   | <10       | <u>dibutyl phthalate</u>               |
| 111-76-2  | <10       | <u>ethylene glycol monobutyl ether</u> |

**SECTION 4 FIRST AID MEASURES****Description of first aid measures**

|                     |   |
|---------------------|---|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> </ul>                        |

## APM AC300 Plastic Paint (Metallic Colors)

|                  |   |
|------------------|---|
|                  | <ul style="list-style-type: none"> <li>▶ Transport to hospital, or doctor.</li> </ul>   |
| <b>Ingestion</b> | <ul style="list-style-type: none"> <li>▶ If swallowed do <b>NOT</b> induce vomiting.</li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul> |

**Indication of any immediate medical attention and special treatment needed**

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to ethylene glycol:

- ▶ Early treatment of ingestion is important. Ensure emesis is satisfactory.
- ▶ Test and correct for metabolic acidosis and hypocalcaemia.
- ▶ Apply sustained diuresis when possible with hypertonic mannitol.
- ▶ Evaluate renal status and begin haemodialysis if indicated. [I.L.O]
- ▶ Rapid absorption is an indication that emesis or lavage is effective only in the first few hours. Cathartics and charcoal are generally not effective.
- ▶ Correct acidosis, fluid/electrolyte balance and respiratory depression in the usual manner. Systemic acidosis (below 7.2) can be treated with intravenous sodium bicarbonate solution.
- ▶ Ethanol therapy prolongs the half-life of ethylene glycol and reduces the formation of toxic metabolites.
- ▶ Pyridoxine and thiamine are cofactors for ethylene glycol metabolism and should be given (50 to 100 mg respectively) intramuscularly, four times per day for 2 days.
- ▶ Magnesium is also a cofactor and should be replenished. The status of 4-methylpyrazole, in the treatment regime, is still uncertain. For clearance of the material and its metabolites, haemodialysis is much superior to peritoneal dialysis.

[Ellenhorn and Barceloux: Medical Toxicology]

It has been suggested that there is a need for establishing a new biological exposure limit before a workshift that is clearly below 100 mmol ethoxy-acetic acids per mole creatinine in morning urine of people occupationally exposed to ethylene glycol ethers. This arises from the finding that an increase in urinary stones may be associated with such exposures.

Laitinen J., et al: *Occupational & Environmental Medicine* 1996; 53, 595-600

for simple esters:

**BASIC TREATMENT**

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

**ADVANCED TREATMENT**

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

**EMERGENCY DEPARTMENT**

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. *EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994*

**SECTION 5 FIREFIGHTING MEASURES****Extinguishing media**

|  |   |
|--|---|
|  | <ul style="list-style-type: none"> <li>▶ Foam.</li> <li>▶ Dry chemical powder.</li> <li>▶ BCF (where regulations permit).</li> <li>▶ Carbon dioxide.</li> <li>▶ Water spray or fog - Large fires only.</li> </ul> |
|--|---|

**Special hazards arising from the substrate or mixture**

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

**Advice for firefighters**

|                      |  |
|----------------------|--|
| <b>Fire Fighting</b> | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ Fight fire from a safe distance, with adequate cover.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</li> </ul> |
|----------------------|--|

## APM AC300 Plastic Paint (Metallic Colors)

|                              |   |
|------------------------------|---|
|                              | <ul style="list-style-type: none"> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>Do not approach containers suspected to be hot.</b></li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul>   |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include; carbon dioxide (CO<sub>2</sub>) metal oxides other pyrolysis products typical of burning organic material</p> |

### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> <li>▶ Collect residues in a flammable waste container.</li> </ul>  |
| <b>Major Spills</b> | <p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse /absorb vapour.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Use only spark-free shovels and explosion proof equipment.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |
|                     | <p>Personal Protective Equipment advice is contained in Section 8 of the SDS.</p>  |

### SECTION 7 HANDLING AND STORAGE

#### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> <li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>▶ Vapour may ignite on pumping or pouring due to static electricity.</li> <li>▶ <b>DO NOT use plastic buckets.</b></li> <li>▶ Earth and secure metal containers when dispensing or pouring product.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this MSDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this MSDS.</li> </ul>   |

#### Conditions for safe storage, including any incompatibilities

|                           |  |
|---------------------------|--|
| <b>Suitable container</b> | <ul style="list-style-type: none"> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ Check that containers are clearly labelled and free from leaks.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can</li> </ul> |
|---------------------------|--|

## APM AC300 Plastic Paint (Metallic Colors)

|                                |   |
|--------------------------------|---|
|                                | <ul style="list-style-type: none"> <li>▶ must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li> <li>▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li> <li>▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</li> <li>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid strong acids, bases.</li> <li>▶ Avoid reaction with oxidising agents</li> </ul>  |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

| Source  | Ingredient                      | Material name          | TWA                              | STEL                            | Peak          | Notes         |
|---|---------------------------------|------------------------|----------------------------------|---------------------------------|---------------|---------------|
| Singapore Permissible Exposure Limits of Toxic Substances | n-butyl acetate                 | n-Butyl acetate        | 713 mg/m <sup>3</sup> / 150 ppm  | 200 mg/m <sup>3</sup> / 950 ppm | Not Available | Not Available |
| Singapore Permissible Exposure Limits of Toxic Substances | ethyl acetate                   | Ethyl acetate          | 1440 mg/m <sup>3</sup> / 400 ppm | Not Available                   | Not Available | Not Available |
| Singapore Permissible Exposure Limits of Toxic Substances | aluminium flake                 | Aluminium Metal dust   | 10 mg/m <sup>3</sup>             | Not Available                   | Not Available | Not Available |
| Singapore Permissible Exposure Limits of Toxic Substances | dibutyl phthalate               | Dibutyl phthalate      | 5 mg/m <sup>3</sup>              | Not Available                   | Not Available | Not Available |
| Singapore Permissible Exposure Limits of Toxic Substances | ethylene glycol monobutyl ether | 2-Butoxyethanol (EGBE) | 121 mg/m <sup>3</sup> / 25 ppm   | Not Available                   | Not Available | Not Available |


## EMERGENCY LIMITS

| Ingredient                      | Material name                        | TEEL-1               | TEEL-2               | TEEL-3                 |
|---------------------------------|--------------------------------------|----------------------|----------------------|------------------------|
| n-butyl acetate                 | Butyl acetate, n-                    | Not Available        | Not Available        | Not Available          |
| ethyl acetate                   | Ethyl acetate                        | 400 ppm              | 400 ppm              | 10000 ppm              |
| aluminium flake                 | Aluminum                             | 3 mg/m <sup>3</sup>  | 33 mg/m <sup>3</sup> | 200 mg/m <sup>3</sup>  |
| dibutyl phthalate               | Dibutyl phthalate                    | 15 mg/m <sup>3</sup> | 31 mg/m <sup>3</sup> | 9300 mg/m <sup>3</sup> |
| ethylene glycol monobutyl ether | Butoxyethanol, 2-; (Glycol ether EB) | 20 ppm               | 20 ppm               | 700 ppm                |

| Ingredient                      | Original IDLH           | Revised IDLH            |
|---------------------------------|-------------------------|-------------------------|
| n-butyl acetate                 | 10,000 ppm              | 1,700 [LEL] ppm         |
| ethyl acetate                   | 10,000 ppm              | 2,000 [LEL] ppm         |
| aluminium flake                 | Not Available           | Not Available           |
| dibutyl phthalate               | 9,300 mg/m <sup>3</sup> | 4,000 mg/m <sup>3</sup> |
| ethylene glycol monobutyl ether | 700 ppm                 | 700 [Unch] ppm          |

## Exposure controls

|   |  |                                 |
|---|--|---------------------------------|
| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> |                                 |
|   | Type of Contaminant:   | Air Speed:                      |
|   | solvent, vapours, degreasing etc., evaporating from tank (in still air).   | 0.25-0.5 m/s<br>(50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)  |                                 |

|  | <p>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</p> <p style="text-align: right;">1-2.5 m/s<br/>(200-500 f/min.)</p> <p>Within each range the appropriate value depends on:</p> <table border="1" data-bbox="359 324 1484 492"> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>   | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|--|---|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
| Lower end of the range                                     | Upper end of the range  |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture      | 1: Disturbing room air currents   |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity  |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.                           | 3: High production, heavy use   |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion                  | 4: Small hood-local control only  |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Personal protection</b></p>                          |    |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Eye and face protection</b></p>                      | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Skin protection</b></p>                              | <p>See Hand protection below</p>  |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Hands/feet protection</b></p>                        | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>For esters:</p> <ul style="list-style-type: none"> <li>▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>▶ frequency and duration of contact,</li> <li>▶ chemical resistance of glove material,</li> <li>▶ glove thickness and</li> <li>▶ dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>▶ When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>▶ When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>▶ Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>▶ Contaminated gloves should be replaced.</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Body protection</b></p>                              | <p>See Other protection below</p>   |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Other protection</b></p>                             | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> </ul> <p>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</p> <p>Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</p>  |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <p><b>Thermal hazards</b></p>                              | <p>Not Available</p>  |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |

**Recommended material(s)**

**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

APM AC300 Plastic Paint (Metallic Colors)

| Material | CPI     |
|----------|---------|
| ##ethyl  | acetate |

**Respiratory protection**

Type A Filter of sufficient capacity, (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
|                                    |                      |                      |                        |

## APM AC300 Plastic Paint (Metallic Colors)

|                             |           |
|-----------------------------|-----------|
| PE/EVAL/PE                  | A         |
| BUTYL                       | C         |
| BUTYL/NEOPRENE              | C         |
| CPE                         | C         |
| HYPALON                     | C         |
| NAT+NEOPR+NITRILE           | C         |
| NATURAL RUBBER              | C         |
| NATURAL+NEOPRENE            | C         |
| NEOPRENE                    | C         |
| NEOPRENE/NATURAL            | C         |
| NITRILE                     | C         |
| NITRILE+PVC                 | C         |
| PE                          | C         |
| PVA                         | C         |
| PVC                         | C         |
| SARANEX-23                  | C         |
| SARANEX-23 2-PLY            | C         |
| TEFLON                      | C         |
| VITON                       | C         |
| VITON/BUTYL                 | C         |
| VITON/CHLOROBUTYL           | C         |
| ##ethylene glycol monobutyl | ether     |
| ##dibutyl                   | phthalate |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

|               |                 |            |                      |
|---------------|-----------------|------------|----------------------|
| up to 5 x ES  | A-AUS / Class 1 | -          | A-PAPR-AUS / Class 1 |
| up to 25 x ES | Air-line*       | A-2        | A-PAPR-2             |
| up to 50 x ES | -               | A-3        | -                    |
| 50+ x ES      | -               | Air-line** | -                    |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|   |  |  |                |
|---|--|--|----------------|
| <b>Appearance</b>                                   | Coloured highly flammable liquid with a characteristic odour; does not mix with water. |  |                |
| <b>Physical state</b>                               | Liquid   | <b>Relative density (Water = 1)</b>            | 0.95-1.05      |
| <b>Odour</b>  | Not Available  | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available  | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Applicable   | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available  | <b>Viscosity (cSt)</b>                         | 65-70 KU       |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available  | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | -4.4   | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | HIGHLY FLAMMABLE.  | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available  | <b>Volatile Component (%vol)</b>               | 70-80          |
| <b>Vapour pressure (kPa)</b>                        | Not Available  | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Immiscible   | <b>pH as a solution (1%)</b>                   | Not Applicable |
| <b>Vapour density (Air = 1)</b>                     | Not Available  | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 STABILITY AND REACTIVITY

|                           |  |
|---------------------------|--|
| <b>Reactivity</b>         | See section 7  |
| <b>Chemical stability</b> | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |

## APM AC300 Plastic Paint (Metallic Colors)

|   |               |
|---|---------------|
| <b>Possibility of hazardous reactions</b> | See section 7 |
| <b>Conditions to avoid</b>                | See section 7 |
| <b>Incompatible materials</b>             | See section 7 |
| <b>Hazardous decomposition products</b>   | See section 5 |

### SECTION 11 TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Exposure to 400ppm ethyl acetate may cause mild eye, nose and throat irritation in an unacclimated persons. However, production workers with regular exposure have better tolerance.</p> <p>Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.</p>   |
| <b>Ingestion</b>    | <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Acute intoxication by ethyl acetate causes impaired co-ordination, exhilaration, slurred speech, nausea, vomiting, and may progress to stupor, coma and death from failure of breathing or blood circulation.</p> <p>The toxicity of phthalates is not excessive due to slow oral absorption and metabolism. Absorption is affected by fat in the diet. Repeated doses can cause cumulative toxic effects, and symptoms include an enlarged liver which often reverses if exposure is maintained. Carbohydrate metabolism is disrupted, and cholesterol and triglyceride levels in the blood falls. In rats, there is also strong evidence of withering of the testicles. Some phthalates can increase the effects of antibiotics, thiamine (vitamin B1) and sulfonamides.</p> |
| <b>Skin Contact</b> | <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.</p> <p>Though considered non-harmful, slight irritation may result from contact because of the abrasive nature of the aluminium oxide particles. Thus it may cause itching and skin reaction and inflammation.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>   |
| <b>Eye</b>          | <p>This material can cause eye irritation and damage in some persons.</p>  |
| <b>Chronic</b>      | <p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.</p> <p>Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Oral or intraperitoneal administration of dibutyl phthalate, at high doses produced a number of bone resorptions, neural tube defects, skeletal abnormalities and increased foetal deaths.</p> <p>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.</p>   |

| APM AC300 Plastic Paint (Metallic Colors)   | TOXICITY   | IRRITATION   |
|---|--|--|
|   | Not Available  | Not Available  |
| n-butyl acetate                             | TOXICITY   | IRRITATION   |
|   | Dermal (rabbit) LD50: >14080 mg/kg <sup>[1]</sup>    | * [PPG]  |
|   | Inhalation (rat) LC50: 2000 ppm/4H <sup>[2]</sup>    | Eye (human): 300 mg  |
|   | Inhalation (rat) LC50: 390 ppm/4h <sup>[2]</sup>     | Eye (rabbit): 20 mg (open)-SEVERE  |
|   | Oral (rat) LD50: 10736 mg/kg <sup>[1]</sup>          | Eye (rabbit): 20 mg/24h - moderate<br>Skin (rabbit): 500 mg/24h-moderate |
| ethyl acetate                               | TOXICITY   | IRRITATION   |
|   | Dermal (rabbit) LD50: >18000 mg/kg <sup>[2]</sup>    | Eye (human): 400 ppm   |
|   | Inhalation (mouse) LC50: >18 mg/14 h <sup>[1]</sup>  |  |
|   | Inhalation (mouse) LC50: 33.5 mg/12 h <sup>[1]</sup> |  |
|   | Inhalation (mouse) LC50: 45 mg/L/2H <sup>[2]</sup>   |  |
|   | Inhalation (rat) LC50: >6000 ppm/6H <sup>[2]</sup>   |  |
|   | Inhalation (rat) LC50: 1600 ppm/8h <sup>[2]</sup>    |  |
|   | Inhalation (rat) LC50: 200 mg/11 h <sup>[1]</sup>    |  |
| Oral (rat) LD50: 10170 mg/kg <sup>[1]</sup> |  |  |
| aluminium flake                             | TOXICITY   | IRRITATION   |
|   | Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>          | Not Available  |
| dibutyl phthalate                           | TOXICITY   | IRRITATION   |
|   | Dermal (rabbit) LD50: >21000 mg/kg <sup>[2]</sup>    | Not Available  |
|   | Inhalation (mouse) LC50: 25 mg/L/2H <sup>[2]</sup>   |  |



## APM AC300 Plastic Paint (Metallic Colors)

|   | Oral (rat) LD50: 6279 mg/kg <sup>[1]</sup>   |                             |            |   |                   |  |                             |   |  |
|---|--|-----------------------------|------------|---|-------------------|--|-----------------------------|---|--|
| ethylene glycol monobutyl ether           | <table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: &gt;2000 mg/kg<sup>[1]</sup></td> <td>* [Union Carbide]</td> </tr> <tr> <td>Inhalation (rat) LC50: 450 ppm/4H<sup>[2]</sup></td> <td>Eye (rabbit): 100 mg SEVERE</td> </tr> <tr> <td>Oral (rat) LD50: 250 mg/kg<sup>[2]</sup></td> <td>Eye (rabbit): 100 mg/24h-moderate<br/>Skin (rabbit): 500 mg, open; mild</td> </tr> </tbody> </table>   | TOXICITY                    | IRRITATION | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup> | * [Union Carbide] | Inhalation (rat) LC50: 450 ppm/4H <sup>[2]</sup> | Eye (rabbit): 100 mg SEVERE | Oral (rat) LD50: 250 mg/kg <sup>[2]</sup> | Eye (rabbit): 100 mg/24h-moderate<br>Skin (rabbit): 500 mg, open; mild |
|   | TOXICITY   | IRRITATION                  |            |   |                   |  |                             |   |  |
|   | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>  | * [Union Carbide]           |            |   |                   |  |                             |   |  |
|   | Inhalation (rat) LC50: 450 ppm/4H <sup>[2]</sup>   | Eye (rabbit): 100 mg SEVERE |            |   |                   |  |                             |   |  |
| Oral (rat) LD50: 250 mg/kg <sup>[2]</sup> | Eye (rabbit): 100 mg/24h-moderate<br>Skin (rabbit): 500 mg, open; mild   |                             |            |   |                   |  |                             |   |  |
| <b>Legend:</b>                            | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances  |                             |            |   |                   |  |                             |   |  |
| N-BUTYL ACETATE                           | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.<br>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.   |                             |            |   |                   |  |                             |   |  |
| ALUMINIUM FLAKE                           | No significant acute toxicological data identified in literature search.   |                             |            |   |                   |  |                             |   |  |
| DIBUTYL PHTHALATE                         | <p>For dibutyl phthalate (DBP):</p> <p>In studies on rats, DBP is absorbed through the skin, although in <i>in vitro</i> studies human skin has been found to be less permeable than rat skin to this compound. Studies in laboratory animals indicate that DBP is rapidly absorbed from the gastrointestinal tract, distributed primarily to the liver and kidneys of rats and excreted in urine as metabolites following oral or intravenous administration. Following inhalation, it was consistently detected at low concentrations in the brain. Available data indicate that in rats, following ingestion, DBP is metabolised by nonspecific esterases mainly in the small intestine to yield mono- <i>n</i>-butyl phthalate (MBP) with limited subsequent biochemical oxidation of the alkyl side chain of MBP. MBP is stable and resistant to hydrolysis of the second ester group. Accumulation has not been observed in any organ. The profile of effects following exposure to DBP is similar to that of other phthalate esters, which, in susceptible species, can induce hepatomegaly, increased numbers of hepatic peroxisomes, foetotoxicity, teratogenicity and testicular damage.</p> <p><b>Acute toxicity:</b> The acute toxicity of DBP in rats and mice is low. Signs of acute toxicity in laboratory animals include depression of activity, laboured breathing and lack of coordination. In a case of accidental poisoning of a worker who ingested approximately 10 grams of DBP, recovery was gradual within two weeks and complete after 1 month.</p> <p>On the basis of limited available data in animal species, DBP appears to have little potential to irritate skin or eyes or to induce sensitization. In humans, a few cases of sensitization after exposure to DBP have been reported, although this was not confirmed in controlled studies of larger numbers of individuals reported only in secondary accounts</p> <p><b>Repeat dose toxicity:</b> In short-term repeated-dose toxicity studies, effects at lowest levels in rats after oral administration for 5 to 21 days included peroxisome proliferation and hepatomegaly at doses of 420 mg/kg body weight per day or more. In longer-term studies, the effects in rats observed following ingestion of DBP for periods up to 7 months included reduced rate of weight gain at doses of 250 mg/kg body weight per day or more. Increase in relative liver weight has been observed at doses of 120 mg/kg body weight or more. Peroxisomal proliferation with increased peroxisomal enzyme activity has been observed at doses of 279 mg/kg body weight per day or more. Necrotic hepatic changes in Wistar rats have been reported at doses of 250 mg/kg body weight per day or more but not in F-344 or Sprague-Dawley rats exposed to up to 2500 mg/kg body weight per day. Alteration in testicular enzymes and degeneration of testicular germinal cells of rats have been observed at doses of 250 and 571 mg/kg body weight per day. There are considerable species differences in effects on the testes following exposure to DBP, minimal effects being observed in mice and hamsters at doses as high as 2000 mg/kg body weight per day. In mice, effects on body and organ weights and histological alterations in the liver indicative of metabolic stress have been reported in a recent subchronic bioassay, for which the no-observed-effect-level (NOEL) was 353 mg/kg body weight per day.</p> <p><b>Developmental toxicity:</b> . In a continuous breeding protocol, which included cross-over mating and offspring assessment phases, rats were exposed to 0, 1000, 5000 or 10 000 mg DBP/kg in the diet (equivalent to 0, 66, 320 and 651 mg/kg body weight per day). In the first generation the reduction in pup weight in the mid-dose group, in the absence of any adverse effect on maternal weight, could be regarded as a developmental toxicity effect. There was also a significant reduction of live litter numbers at all three dose levels. The effects in the second generation were more severe, with reduced pup weight in all groups including the low-dose group, structural defects (such as prepuccial/ penile malformations, seminiferous tubule degeneration, and absence or underdevelopment of the epididymides) in the mid- and high-dose groups, and severe effects on spermatogenesis in the high-dose group that were not seen in the parent animals. These results suggest that the adverse effects of DBP are more marked in animals exposed during development and maturation than in animals exposed as adults only. No clear NOEL was established in this study. The lowest-observed- adverse-effect-level (LOAEL) was considered to be 66 mg/kg body weight per day. The available studies show that DBP generally induces foetotoxic effects in the absence of maternal toxicity. Available data also indicate that DBP is teratogenic at high doses and that susceptibility to teratogenesis varies with developmental stage and period of administration. In mice, DBP caused dose-dependent increases in the number of resorptions and dead fetuses at oral doses of 400 mg/kg body weight per day or more. Dose-dependent decreases in fetal weights and number of viable litters were also observed in mice at these doses. Adequate carcinogenesis bioassays for DBP have not been conducted. The weight of the available evidence indicates that DBP is not genotoxic.</p> <p>The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.</p> <p>Available data indicate that phthalate esters are minimally toxic by swallowing, inhalation and skin contact. Repeated exposure may result in weight gain, liver enlargement and induction of liver enzymes. They may also cause shrinking of the testicles and other structural malformations. They may reduce male and female fertility and number of live births, according to animal testing.</p> |                             |            |   |                   |  |                             |   |  |
| ETHYLENE GLYCOL MONOBUTYL ETHER           | <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>For ethylene glycol monoalkyl ethers and their acetates (EGMAEs):</p> <p>Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE) and their acetates.</p> <p>EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol ethers.</p> <p><b>Acute Toxicity:</b> Oral LD50 values in rats for all category members range from 739 (EGHE) to 3089 mg/kg bw (EGPE), with values increasing with decreasing molecular weight. Four to six hour acute inhalation toxicity studies were conducted for these chemicals in rats at the highest vapour concentrations practically achievable. Values range from LC0 &gt; 85 ppm (508 mg/m<sup>3</sup>) for EGHE, LC50 &gt; 400ppm (2620 mg/m<sup>3</sup>) for EGBEA to LC50 &gt; 2132 ppm (9061 mg/m<sup>3</sup>) for EGPE. No lethality was observed for any of these materials under these conditions. Dermal LD50 values in rabbits range from 435 mg/kg bw (EGBE) to 1500 mg/kg bw (EGBEA). Overall these category members can be considered to be of low to moderate acute toxicity. All category members cause reversible irritation to skin and eyes, with EGBEA less irritating and EGHE more irritating than the other category members. EGPE and EGBE are not sensitizers in experimental animals or humans. Signs of acute toxicity in rats, mice and rabbits are consistent with haemolysis (with the exception of EGHE) and non-specific CNS depression typical of organic solvents in general. Alkoxyacetic acid metabolites, propoxyacetic acid (PAA) and butoxyacetic acid (BAA), are responsible for the red blood cell hemolysis. Signs of toxicity in humans deliberately ingesting cleaning fluids containing</p>   |                             |            |   |                   |  |                             |   |  |

## APM AC300 Plastic Paint (Metallic Colors)

9-22% EGBE are similar to those of rats, with the exception of haemolysis. Although decreased blood haemoglobin and/or haemoglobinuria were observed in some of the human cases, it is not clear if this was due to haemolysis or haemodilution as a result of administration of large volumes of fluid. Red blood cells of humans are many-fold more resistant to toxicity from EGPE and EGBE *in vitro* than those of rats.

**Repeat dose toxicity:** The fact that the NOAEL for repeated dose toxicity of EGBE is less than that of EGPE is consistent with red blood cells being more sensitive to EGBE than EGPE. Blood from mice, rats, hamsters, rabbits and baboons were sensitive to the effects of BAA *in vitro* and displayed similar responses, which included erythrocyte swelling (increased haematocrit and mean corpuscular hemoglobin), followed by hemolysis. Blood from humans, pigs, dogs, cats, and guinea pigs was less sensitive to haemolysis by BAA *in vitro*.

**Mutagenicity:** In the absence and presence of metabolic activation, EGBE tested negative for mutagenicity in Ames tests conducted in *S. typhimurium* strains TA97, TA98, TA100, TA1535 and TA1537 and EGHE tested negative in strains TA98, TA100, TA1535, TA1537 and TA1538. *In vitro* cytogenetic and sister chromatid exchange assays with EGBE and EGHE in Chinese Hamster Ovary Cells with and without metabolic activation and *in vivo* micronucleus tests with EGBE in rats and mice were negative, indicating that these glycol ethers are not genotoxic.

**Carcinogenicity:** In a 2-year inhalation chronic toxicity and carcinogenicity study with EGBE in rats and mice a significant increase in the incidence of liver haemangiosarcomas was seen in male mice and forestomach tumours in female mice. It was decided that based on the mode of action data available, there was no significant hazard for human carcinogenicity.

**Reproductive and developmental toxicity.** The results of reproductive and developmental toxicity studies indicate that the glycol ethers in this category are not selectively toxic to the reproductive system or developing fetus, developmental toxicity is secondary to maternal toxicity. The repeated dose toxicity studies in which reproductive organs were examined indicate that the members of this category are not associated with toxicity to reproductive organs (including the testes).

Results of the developmental toxicity studies conducted via inhalation exposures during gestation periods on EGPE (rabbits -125, 250, 500 ppm or 531, 1062, or 2125 mg/m<sup>3</sup> and rats - 100, 200, 300, 400 ppm or 425, 850, 1275, or 1700 mg/m<sup>3</sup>), EGBE (rat and rabbit - 25, 50, 100, 200 ppm or 121, 241, 483, or 966 mg/m<sup>3</sup>), and EGHE (rat and rabbit - 20.8, 41.4, 79.2 ppm or 124, 248, or 474 mg/m<sup>3</sup>) indicate that the members of the category are not teratogenic. The NOAELs for developmental toxicity are greater than 500 ppm or 2125 mg/m<sup>3</sup> (rabbit-EGPE), 100 ppm or 425 mg/m<sup>3</sup> (rat-EGPE), 50 ppm or 241 mg/m<sup>3</sup> (rat EGBE) and 100 ppm or 483 mg/m<sup>3</sup> (rabbit EGBE) and greater than 79.2 ppm or 474 mg/m<sup>3</sup> (rat and rabbit-EGHE).

Exposure of pregnant rats to ethylene glycol monobutyl ether (2-butoxyethanol) at 100 ppm or rabbits at 200 ppm during organogenesis resulted in maternal toxicity and embryotoxicity including a decreased number of viable implantations per litter. Slight foetotoxicity in the form of poorly ossified or unossified skeletal elements was also apparent in rats. Teratogenic effects were not observed in other species.

At least one researcher has stated that the reproductive effects were less than that of other monoalkyl ethers of ethylene glycol.

Chronic exposure may cause anaemia, macrocytosis, abnormally large red cells and abnormal red cell fragility.

Exposure of male and female rats and mice for 14 weeks to 2 years produced a regenerative haemolytic anaemia and subsequent effects on the haemopoietic system in rats and mice. In addition, 2-butoxyethanol exposures caused increases in the incidence of neoplasms and nonneoplastic lesions (1). The occurrence of the anaemia was concentration-dependent and more pronounced in rats and females. In this study it was proposed that 2-butoxyethanol at concentrations of 500 ppm and greater produced an acute disseminated thrombosis and bone infarction in male and female rats as a result of severe acute haemolysis and reduced deformability of erythrocytes or through anoxic damage to endothelial cells that compromise blood flow. In two-year studies, 2-butoxyethanol continued to affect circulating erythroid mass, inducing a responsive anaemia. Rats showed a marginal increase in the incidence of benign or malignant pheochromocytomas (combined) of the adrenal gland. In mice, 2-butoxyethanol exposure resulted in a concentration dependent increase in the incidence of squamous cell papilloma or carcinoma of the forestomach. It was hypothesised that exposure-induced irritation produced inflammatory and hyperplastic effects in the forestomach and that the neoplasia were associated with a continuation of the injury/ degeneration process. Exposure also produced a concentration -dependent increase in the incidence of haemangiosarcoma of the liver of male mice and hepatocellular carcinoma.

1: NTP Toxicology Program Technical report Series 484, March 2000.

For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed through the gastrointestinal tract. Limited information suggests that it is also absorbed through the respiratory tract; dermal absorption is apparently slow. Following absorption, ethylene glycol is distributed throughout the body according to total body water. In most mammalian species, including humans, ethylene glycol is initially metabolised by alcohol.

dehydrogenase to form glycolaldehyde, which is rapidly converted to glycolic acid and glyoxal by aldehyde oxidase and aldehyde dehydrogenase. These metabolites are oxidised to glyoxylate; glyoxylate may be further metabolised to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate CO<sub>2</sub>, which is one of the major elimination products of ethylene glycol. In addition to exhaled CO<sub>2</sub>, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination of ethylene glycol from the plasma in both humans and laboratory animals is rapid after oral exposure; elimination half-lives are in the range of 1-4 hours in most species tested.

**Respiratory Effects.** Respiratory system involvement occurs 12-24 hours after ingestion of sufficient amounts of ethylene glycol and is considered to be part of a second stage in ethylene glycol poisoning. The symptoms include hyperventilation, shallow rapid breathing, and generalized pulmonary edema with calcium oxalate crystals occasionally present in the lung parenchyma. Respiratory system involvement appears to be dose-dependent and occurs concomitantly with cardiovascular changes. Pulmonary infiltrates and other changes compatible with adult respiratory distress syndrome (ARDS) may characterise the second stage of ethylene glycol poisoning. Pulmonary oedema can be secondary to cardiac failure, ARDS, or aspiration of gastric contents. Symptoms related to acidosis such as hyperpnea and tachypnea are frequently observed; however, major respiratory morbidities such as pulmonary edema and bronchopneumonia are relatively rare and usually only observed with extreme poisoning (e.g., in only 5 of 36 severely poisoned cases).

**Cardiovascular Effects.** Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of oral ethylene glycol poisoning, which is 12- 24 hours after acute exposure. The symptoms of cardiac involvement include tachycardia, ventricular gallop and cardiac enlargement. Ingestion of ethylene glycol may also cause hypertension or hypotension, which may progress to cardiogenic shock. Myocarditis has been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol. As in the case of respiratory effects, cardiovascular involvement occurs with ingestion of relatively high doses of ethylene glycol.

Nevertheless, circulatory disturbances are a rare occurrence, having been reported in only 8 of 36 severely poisoned cases. Therefore, it appears that acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.

**Gastrointestinal Effects.** Nausea, vomiting with or without blood, pyrosis, and abdominal cramping and pain are common early effects of acute ethylene glycol ingestion. Acute effects of ethylene glycol ingestion in one patient included intermittent diarrhea and abdominal pain, which were attributed to mild colonic ischaemia; severe abdominal pain secondary to colonic stricture and perforation developed 3 months after ingestion, and histology of the resected colon showed birefringent crystals highly suggestive of oxalate deposition.

**Musculoskeletal Effects.** Reported musculoskeletal effects in cases of acute ethylene glycol poisoning have included diffuse muscle tenderness and myalgias associated with elevated serum creatinine phosphokinase levels, and myoclonic jerks and tetanic contractions associated with hypocalcaemia.

**Hepatic Effects.** Central hydropic or fatty degeneration, parenchymal necrosis, and calcium oxalate crystals in the liver have been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol.

**Renal Effects.** Adverse renal effects after ethylene glycol ingestion in humans can be observed during the third stage of ethylene glycol toxicity 24-72 hours after acute exposure. The hallmark of renal toxicity is the presence of birefringent calcium oxalate monohydrate crystals deposited in renal tubules and their presence in urine after ingestion of relatively high amounts of ethylene glycol. Other signs of nephrotoxicity can include tubular cell degeneration and necrosis and tubular interstitial inflammation. If untreated, the degree of renal damage caused by high doses of ethylene glycol progresses and leads to haematuria, proteinuria, decreased renal function, oliguria, anuria, and ultimately renal failure. These changes in the kidney are linked to acute tubular necrosis but normal or near normal renal function can return with adequate supportive therapy.

**Metabolic Effects.** One of the major adverse effects following acute oral exposure of humans to ethylene glycol involves metabolic changes. These changes occur as early as 12 hours after ethylene glycol exposure. Ethylene glycol intoxication is accompanied by metabolic acidosis which is manifested by decreased pH and bicarbonate content of serum and other bodily fluids caused by accumulation of excess glycolic acid. Other characteristic metabolic effects of ethylene glycol poisoning are increased serum anion gap, increased osmolal gap, and hypocalcaemia. Serum anion gap is calculated from concentrations of sodium, chloride, and bicarbonate, is normally 12-16 mM, and is typically elevated after ethylene glycol ingestion due to increases in unmeasured metabolite anions (mainly glycolate).

**Neurological Effects:** Adverse neurological reactions are among the first symptoms to appear in humans after ethylene glycol ingestion. These early neurotoxic effects are also the only symptoms attributed to unmetabolised ethylene glycol. Together with metabolic changes, they occur during the period of

## APM AC300 Plastic Paint (Metallic Colors)

30 minutes to 12 hours after exposure and are considered to be part of the first stage in ethylene glycol intoxication. In cases of acute intoxication, in which a large amount of ethylene glycol is ingested over a very short time period, there is a progression of neurological manifestations which, if not treated, may lead to generalized seizures and coma. Ataxia, slurred speech, confusion, and somnolence are common during the initial phase of ethylene glycol intoxication as are irritation, restlessness, and disorientation. Cerebral edema and crystalline deposits of calcium oxalate in the walls of small blood vessels in the brain were found at autopsy in people who died after acute ethylene glycol ingestion.

Effects on cranial nerves appear late (generally 5-20 days post-ingestion), are relatively rare, and according to some investigators constitute a fourth, late cerebral phase in ethylene glycol intoxication. Clinical manifestations of the cranial neuropathy commonly involve lower motor neurons of the facial and bulbar nerves and are reversible over many months.

**Reproductive Effects:** Reproductive function after intermediate-duration oral exposure to ethylene glycol has been tested in three multi-generation studies (one in rats and two in mice) and several shorter studies (15-20 days in rats and mice). In these studies, effects on fertility, foetal viability, and male reproductive organs were observed in mice, while the only effect in rats was an increase in gestational duration.

**Developmental Effects:** The developmental toxicity of ethylene glycol has been assessed in several acute-duration studies using mice, rats, and rabbits. Available studies indicate that malformations, especially skeletal malformations occur in both mice and rats exposed during gestation; mice are apparently more sensitive to the developmental effects of ethylene glycol. Other evidence of embryotoxicity in laboratory animals exposed to ethylene glycol exposure includes reduction in foetal body weight.

**Cancer:** No studies were located regarding cancer effects in humans or animals after dermal exposure to ethylene glycol.

**Genotoxic Effects:** Studies in humans have not addressed the genotoxic effects of ethylene glycol. However, available *in vivo* and *in vitro* laboratory studies provide consistently negative genotoxicity results for ethylene glycol.

NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high concentrations of this substance by all routes. \*\* ASCC (NZ) SDS

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ☹ | Carcinogenicity          | ☹ |
| Skin Irritation/Corrosion         | ☹ | Reproductivity           | ✔ |
| Serious Eye Damage/Irritation     | ✔ | STOT - Single Exposure   | ✔ |
| Respiratory or Skin sensitisation | ☹ | STOT - Repeated Exposure | ☹ |
| Mutagenicity                      | ☹ | Aspiration Hazard        | ☹ |

Legend: ✔ – Data required to make classification available  
 ✘ – Data available but does not fill the criteria for classification  
 ☹ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and/or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and/or delayed, to the structure and/or functioning of natural ecosystems.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For n-Butyl Acetate:

Koc: ~200;

log Kow: 1.78;

Half-life (hr) air: 144;

Half-life (hr) H<sub>2</sub>O surface water: 178 - 27156;

Henry's atm: m<sup>3</sup>/mol: 3.20E-04

BOD 5 if unstated: 0.15-1.02,7%;

COD: 78%;

ThOD: 2.207;

BCF : 4-14.

Environmental Fate: Terrestrial Fate - Butyl acetate is expected to have moderate mobility in soil. Volatilization of n-butyl acetate is expected from moist and dry soil surfaces. n-Butyl acetate may biodegrade in soil. Aquatic Fate: n-Butyl acetate is not expected to adsorb to suspended solids and sediment in water. Butyl acetate is expected to volatilize from water surfaces. Estimated

half-lives for a model river and model lake are 7 and 127 hours respectively. Hydrolysis may be an important environmental fate for this compound. Atmospheric Fate: n-Butyl acetate is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase n-butyl acetate is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 4 days.

Ecotoxicity: It is expected that bioconcentration in aquatic organisms is low. n-Butyl acetate is not acutely toxic to fish specifically, inland silverside, bluegill sunfish, fathead minnow, and water fleas and has low toxicity to algae.

**DO NOT discharge into sewer or waterways.**

## Persistence and degradability

| Ingredient                      | Persistence: Water/Soil   | Persistence: Air             |
|---------------------------------|---------------------------|------------------------------|
| n-butyl acetate                 | LOW                       | LOW                          |
| ethyl acetate                   | LOW (Half-life = 14 days) | LOW (Half-life = 14.71 days) |
| dibutyl phthalate               | LOW (Half-life = 23 days) | LOW (Half-life = 3.08 days)  |
| ethylene glycol monobutyl ether | LOW (Half-life = 56 days) | LOW (Half-life = 1.37 days)  |

## Bioaccumulative potential

| Ingredient                      | Bioaccumulation   |
|---------------------------------|-------------------|
| n-butyl acetate                 | LOW (BCF = 14)    |
| ethyl acetate                   | HIGH (BCF = 3300) |
| dibutyl phthalate               | LOW (BCF = 176)   |
| ethylene glycol monobutyl ether | LOW (BCF = 2.51)  |

## Mobility in soil

## APM AC300 Plastic Paint (Metallic Colors)

| Ingredient                      | Mobility          |
|---------------------------------|-------------------|
| n-butyl acetate                 | LOW (KOC = 20.86) |
| ethyl acetate                   | LOW (KOC = 6.131) |
| dibutyl phthalate               | LOW (KOC = 1460)  |
| ethylene glycol monobutyl ether | HIGH (KOC = 1)    |



### SECTION 13 DISPOSAL CONSIDERATIONS

#### Waste treatment methods

|                                     |   |
|-------------------------------------|---|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and MSDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|-------------------------------------|---|

### SECTION 14 TRANSPORT INFORMATION

#### Labels Required

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant |  |

#### Land transport (UN)

|                                     |  |
|-------------------------------------|--|
| <b>UN number</b>                    | 1263   |
| <b>Packing group</b>                | II   |
| <b>UN proper shipping name</b>      | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| <b>Environmental hazard</b>         | No relevant data   |
| <b>Transport hazard class(es)</b>   | Class : 3<br>Subrisk : Not Applicable  |
| <b>Special precautions for user</b> | Special provisions : 163,367<br>Limited quantity : 5 L   |

#### Air transport (ICAO-IATA / DGR)

|                                   |   |
|-----------------------------------|---|
| <b>UN number</b>                  | 1263  |
| <b>Packing group</b>              | II  |
| <b>UN proper shipping name</b>    | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds) |
| <b>Environmental hazard</b>       | No relevant data  |
| <b>Transport hazard class(es)</b> | ICAO/IATA Class : 3<br>ICAO / IATA Subrisk : Not Applicable   |

|                                     |   |             |
|-------------------------------------|---|-------------|
|                                     | ERG Code  | 3L          |
| <b>Special precautions for user</b> | Special provisions  | A3 A72 A192 |
|                                     | Cargo Only Packing Instructions                           | 364         |
|                                     | Cargo Only Maximum Qty / Pack                             | 60 L        |
|                                     | Passenger and Cargo Packing Instructions                  | 353         |
|                                     | Passenger and Cargo Maximum Qty / Pack                    | 5 L         |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions | Y341        |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack            | 1 L         |

**Sea transport (IMDG-Code / GGVSee)**

|                                     |  |
|-------------------------------------|--|
| <b>UN number</b>                    | 1263   |
| <b>Packing group</b>                | II   |
| <b>UN proper shipping name</b>      | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| <b>Environmental hazard</b>         | Not Applicable   |
| <b>Transport hazard class(es)</b>   | IMDG Class 3   |
|                                     | IMDG Subrisk Not Applicable  |
| <b>Special precautions for user</b> | EMS Number F-E , S-E   |
|                                     | Special provisions 163   |
|                                     | Limited Quantities 5 L   |

**Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code**

| Source  | Ingredient        | Pollution Category |
|---|-------------------|--------------------|
| IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk | n-butyl acetate   | Y                  |
| IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk | ethyl acetate     | Z                  |
| IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk | dibutyl phthalate | X                  |

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture****N-BUTYL ACETATE(123-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Singapore Permissible Exposure Limits of Toxic Substances

**ETHYL ACETATE(141-78-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Singapore Permissible Exposure Limits of Toxic Substances

**ALUMINIUM FLAKE(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Singapore Permissible Exposure Limits of Toxic Substances

**DIBUTYL PHTHALATE(84-74-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Singapore Permissible Exposure Limits of Toxic Substances

**ETHYLENE GLYCOL MONOBUTYL ETHER(111-76-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

Singapore Permissible Exposure Limits of Toxic Substances

| National Inventory            | Status  |
|-------------------------------|---|
| Australia - AICS              | Y   |
| Canada - DSL                  | Y   |
| Canada - NDSL                 | N (n-butyl acetate; ethyl acetate; aluminium flake; ethylene glycol monobutyl ether; dibutyl phthalate) |
| China - IECSC                 | Y   |
| Europe - EINEC / ELINCS / NLP | Y   |
| Japan - ENCS                  | N (aluminium flake)   |
| Korea - KECI                  | Y   |
| New Zealand - NZIoC           | Y   |
| Philippines - PICCS           | Y   |
| USA - TSCA                    | Y   |

**Legend:**

Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

**SECTION 16 OTHER INFORMATION****Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.