

Product Description

Natural oil treatment for garden decks, furniture and wood flooring

Recommended Use

Interior or exterior wood surfaces
Regular treatments every 6 – 9 months is recommended

Features

Easy application
Water repellent
Fungus resistant

Physical Characteristics

| | | |
|------------------------------|-------------------------|--|
| Recommended Application Data | Dry Film Thickness (µm) | Theoretical Coverage (m ² /l) |
| | 20 µm | 18 - 22 |
| Specific Gravity (For Clear) | Approx. 0.93 | |
| Flash Point | 35 °C | |
| Finish | Matt or Gloss | |
| Color Range | Clear or Colors | |
| Standard Packing Size | 1 L / 5 L | |
| Shelf Life | 12 months | |

Application Method

| | |
|-----------------|--------------------------------|
| Brush and cloth | Suitable method of application |
| Thinning Ratio | None required, Ready to use |

Drying Time

| | | | | |
|-------------|----------|----------|----------------------|----------------|
| Touch Dry | Hard Dry | Full Dry | Overcoating Interval | |
| | | | Minimum | Maximum |
| 6 – 8 hours | 1 day | 7 days | 1 day | Not applicable |

Useful Information

| | |
|----------|---|
| Thinner | Not applicable |
| Cleaner | Turpentine |
| Storage | Store in a cool shaded dry area |
| Disposal | <p>Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate Environmental Quality Regulations.</p> <p>All cloths used in application must be immersed in water prior to disposal to prevent spontaneous combustion.</p> |

Surface Preparation

Dry sand to bare wood.
Sand along the wood grain using medium fine paper to eliminate all loose particles and raised grains.
Clean the surface with cloth.
Apply 1st coat of APILAC Wood Oil. When the surface is saturated, wipe off all excess with a cotton cloth. Work the oil into the wood by rubbing along the wood grain.
Allow it to dry for 1 day.
Apply 2nd coat of APILAC Wood Oil.
Allow at least 24 hours drying time before taking the decking into use. Avoid foot traffic during this time. If it rains on the decking before the oil has hardened, it may be necessary to re-apply a thin layer of oil.

Coating Specifications

| 1 st Coat | 2 nd Coat | 3 rd Coat | 4 th Coat |
|----------------------|----------------------|----------------------|----------------------|
| APILAC Wood Oil | APILAC Wood Oil | | |

Notes

The coating specifications provided above are typical. For specific recommendations to suit individual applications, please refer to your Asia Paint Representative.
Do not proceed with application if rain is expected within 4 hours
Stir the product well before use.

Safety Precaution

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.
Do not use in poorly ventilated areas, do not breathe in vapor or spray mist.
This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge.
In case of fire, use carbon dioxide, normal foam or dry agent.

First Aid

| | |
|--|--|
| Eyes | Wash off in flowing water or shower |
| Skin | Flush with plenty of water |
| Inhalation | Remove to fresh air, loosen collar and keep patient rested |
| Ingestion | If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel |
| For further safety information, please refer to our Safety Data Sheet (SDS) | |

Disclaimer

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.