

Product Description

Air drying type modified chlorinated rubber paint used for road marking on concrete and asphalt surfaces

Recommended Use

For painting traffic lanes, pedestrian crossings, kerb edges, parking divisions, railway platform edges, garages and tennis court markings etc.

Features

Fast drying
Excellent abrasion resistance
Excellent waster resistance
Excellent petrol / diesel / oil resistance

Physical Characteristics

	Theoretical Coverage
Recommended Application Data	Approx. 130 linear meter of 10 centimeter line at 125 microns dry film thickness per 5L. The practical coverage may be 70 ~ 80% of the theoretical value, depending on surface conditions and wastage.
Specific Gravity	0.95 – 1.00
Flash Point	4 °C
Finish	Matt
Color Range	White, Yellow or Red
Standard Packing Size	5L
Shelf Life	24 months

Application Method

Brush or Roller	Recommended method of application
Thinning Ratio	Ready to use. If thinning is desired, do not exceed 10% by volume

Drying Time At 30°C

Touch Dry	Hard Dry	Overcoating Interval	
		Minimum	Maximum
5 minutes	20 minutes	3 hours	Not applicable

Useful Information

Thinner	APM TT 600 Thinner
Cleaner	APM TT 600 Thinner
Storage	Store in a cool shaded dry area
Disposal	Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate Environmental Quality Regulations.

Surface Preparation

The service and life span and the service performance of paints are directly related to the degree of surface preparation.
New concrete should be left for at least 21 days to cure before coating.
The moisture content of the concrete surface should be below 6% prior to application
Ensure that the surface to be overcoated is clean, dry and free from dust, grease, oil, or any other surface contaminants.
Remove dirt and dust by dry brushing. A fresh water wash is recommended.

Coating Specifications

1 st Coat	2 nd Coat		
APM S222 Road Line Paint	APM S222 Road Line Paint		

Notes

The coating specifications provided above are typical. For specific recommendations to suit individual applications, please refer to your Asia Paint Representative.
Stir the product well before use.

Safety Precaution

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.
Do not use in poorly ventilated areas, do not breathe in vapor or spray mist.
This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge.
In case of fire, use carbon dioxide, normal foam or dry agent.

First Aid

Eyes	Wash off in flowing water or shower
Skin	Flush with plenty of water
Inhalation	Remove to fresh air, loosen collar and keep patient rested
Ingestion	If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel
For further safety information, please refer to our Safety Data Sheet (SDS)	

Disclaimer

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.