



Safety Data Sheet dated 8/4/2011, version 1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Mixture identification:

Trade name: TIDILACK BIANCO

Trade code: 1285000

1.2 Relevant identified uses of the substance/mixture and uses advised against

Product type and use: varnishing product

1.3 Details of the supplier of the safety data sheet

Supplier:

INVEBI international sas 21040 Orago (VA) - ITALY - Via varesina 78/B - tel. 39-331-218018/217004 - fax 39-331-216484

Competent person responsible for the safety data sheet:

lab@invebi.it

1.4 Emergency telephone number

INVEBI international sas tel. 39-0331-218018/217004 Fax. +39-0331-216484

Poison Centre - Ospedale di Niguarda - Milan - Tel. 02/66101029

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

Xn Harmful

R Phrases:

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R65 Harmful: may cause lung damage if swallowed.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2 Label elements



Xn

Symbols:

Xn Harmful

R Phrases:

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R65 Harmful: may cause lung damage if swallowed.

S Phrases:

S23 Do not breathe gas/vapour

S25 Avoid contact with eyes.

S36/37 Wear suitable protective clothing and gloves.

Safety Data Sheet

TIDILACK BIANCO

S43 In case of fire, use: dust chemistry, foam, carbonic anhydride.

S51 Use only in well-ventilated areas.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3 Other hazards

Other Hazards:

No other hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

N.A.


3.2 Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and corresponding classification:

10% - 12.5% o-xylene

N.67/548/EEC: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7

Xn,Xi; R10-20/21-38

 2.6/3 Flam. Liq. 3 H226

 3.2/2 Skin Irrit. 2 H315


 3.1/4/Dermal Acute Tox. 4 H312

 3.1/4/Inhal Acute Tox. 4 H332

7% - 10% n-butyl acetate

N.67/548/EEC: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1

R10-66-67; substance with a Community workplace exposure limit


 2.6/3 Flam. Liq. 3 H226

 3.8/3 STOT SE 3 H336

3% - 5% 4-methylpentan-2-one; isobutyl methyl ketone

N.67/548/EEC: 606-004-00-4 CAS: 108-10-1 EC: 203-550-1

F,Xn,Xi; R11-20-36/37-66

 2.6/2 Flam. Liq. 2 H225

 3.3/2 Eye Irrit. 2 H319


 3.8/3 STOT SE 3 H335

 3.1/4/Inhal Acute Tox. 4 H332

1% - 3% 2-methoxy-1-methylethyl acetate

N.67/548/EEC: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9

R10; substance with a Community workplace exposure limit

 2.6/3 Flam. Liq. 3 H226


Safety Data Sheet

TIDILACK BIANCO

1% - 3% toluene

N.67/548/EEC: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9

F,Xn,Xi; R11-38-48/20-63-65-67

 2.6/2 Flam. Liq. 2 H225

 3.7/2 Repr. 2 H361

 3.10/1 Asp. Tox. 1 H304

 3.9/2 STOT RE 2 H373


 3.2/2 Skin Irrit. 2 H315

 3.8/3 STOT SE 3 H336

900 mg/kg acetone; propan-2-one; propanone

N.67/548/EEC: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2

F,Xi; R11-36-66-67

 2.6/2 Flam. Liq. 2 H225

 3.3/2 Eye Irrit. 2 H319

 3.8/3 STOT SE 3 H336

4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the toxin must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2 Most important symptoms and effects, both acute and delayed

None

4.3 Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

Safety Data Sheet

TIDILACK BIANCO

5. FIRE-FIGHTING MEASURES

- 5.1 Extinguishing media
 - Suitable extinguishing media:
CO₂ or Dry chemical fire extinguisher.
 - Extinguishing media which must not be used for safety reasons:
None in particular.
 - 5.2 Special hazards arising from the substance or mixture
 - Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke.
 - 5.3 Advice for fire-fighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove all sources of ignition.
 - Wear breathing apparatus if exposed to vapours/dusts/aerosols.
 - Provide adequate ventilation.
 - Use appropriate respiratory protection.
 - See protective measures under point 7 and 8.
 - 6.2 Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
 - 6.3 Methods and material for containment and cleaning up
 - Wash with plenty of water.
 - 6.4 Reference to other sections
 - See also section 8 and 13
-

7. HANDLING AND STORAGE

- 7.1 Precautions for safe handling:
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Use localized ventilation system.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
 - See also section 8 for recommended protective equipment.
- 7.2 Conditions for safe storage, including any incompatibilities
 - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 - Keep away from food, drink and feed.
 - Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3 Specific end use(s)
 - None in particular

Safety Data Sheet

TIDILACK BIANCO

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

o-xylene - Index: 601-022-00-9, CAS: 1330-20-7, EC No: 215-535-7

VLE 8h: ppm 50 - mg/m³ 221 ,Skin

VLE short: ppm 100 - mg/m³ 442 ,Skin

TLV-TWA: ppm 100 ,A4

TLV-STEL: ppm 150 ,A4

n-butyl acetate - Index: 607-025-00-1, CAS: 123-86-4, EC No: 204-658-1

TLV-TWA: ppm 150

TLV-STEL: ppm 200

4-methylpentan-2-one; isobutyl methyl ketone - Index: 606-004-00-4, CAS: 108-10-1, EC No: 203-550-1

VLE 8h: ppm 20 mg/m³ 83

VLE short: ppm 50 mg/m³ 208

TLV-TWA: ppm 50

TLV-STEL: ppm 75

2-methoxy-1-methylethyl acetate - Index: 607-195-00-7, CAS: 108-65-6, EC No: 203-603-9

VLE 8h: ppm 50 mg/m³ 275 ,Skin

VLE short: ppm 100 mg/m³ 550 ,Skin

toluene - Index: 601-021-00-3, CAS: 108-88-3, EC No: 203-625-9

VLE 8h: ppm 50 mg/m³ 192 ,Skin

VLE short: ppm 100 mg/m³ 384 ,Skin

TLV-TWA: ppm 50 ,Skin A4

TLV-STEL: Skin A4

acetone; propan-2-one; propanone - Index: 606-001-00-8, CAS: 67-64-1, EC No: 200-662-2

VLE 8h: ppm 200 mg/m³ 600

VLE short: ppm 300 mg/m³ 900

TLV-TWA: ppm 200

TLV-STEL: ppm 300

8.2 Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment, e.g. CEN/FFP-2(S) or CEN/FFP-3(S).

Thermal Hazards:

None

Environmental exposure controls:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance and colour: white liquid

Odour: of solvent

Odour threshold: N.A.

Viscosity: FORD N 4 A 20°C=80-90"

Solid content: 70%+-1

Specific weight: 1,400

Solid/gas flammability: N.A.

Safety Data Sheet

TIDILACK BIANCO

Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	+22°C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	N.A.
Solubility in water:	No
Lipid solubility:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	-
Explosive properties:	-
Oxidizing properties:	-
9.2 Other information	
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

None

10.4 Conditions to avoid:

Stable under normal conditions.

10.5 Incompatible materials:

Avoid contact with combustible materials. The product could catch fire.

10.6 Hazardous decomposition products:

None.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

o-xylene - Index: 601-022-00-9, CAS: 1330-20-7, EC No: 215-535-7

OBSERVATIONS ON HUMAN SUBJECTS NON-PROFESSIONAL EXPOSURE -

Effects following acute exposure:

Symptoms of intense exposure are: dermatitis, eczema, irritation to the eyes and to the respiratory tract.

Inhaling the vapours can cause dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

PROFESSIONAL EXPOSURE - Effects following acute exposure:

Narcotic at high concentrations.

Irritation through inhalation at 200 ppm (TCLo). Inhalation of 200 ppm has irritating effects in human subjects.

Human subject (oral)(LDLo): 50 mg/kg.

Inhalatory human subject (LCLo) 10000 ppm/6h.

n-butyl acetate - Index: 607-025-00-1, CAS: 123-86-4, EC No: 204-658-1

OBSERVATIONS ON HUMAN SUBJECTS:

Safety Data Sheet

TIDILACK BIANCO

Inhalation: 3300 ppm (16 mg/l), for short periods, causes serious irritation to the eyes and to the nose.

Inhalation: 200-300 ppm (1-1.4 mg/l), for short periods, cause moderate irritation to the eyes and to the nose.

Inhaling the vapours can irritate the respiratory system.

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2,000 ppm for 60 min.

TCLo: 200 ppm

toluene - Index: 601-021-00-3, CAS: 108-88-3, EC No: 203-625-9

OBSERVATIONS ON HUMAN SUBJECTS - NON-PROFESSIONAL EXPOSURE

Effects following acute exposure:

At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.

At 400 ppm: worsening of symptoms and mental confusion.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Adopt sound working practices, so that the product is not released into the environment.

12.2 Persistence and degradability

None

12.3 Bioaccumulative potential

N.A.

12.4 Mobility in soil

N.A.

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

14.1 UN number:

ADR-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

14.2 UN proper shipping name:

ADR-Shipping Name: PAINT or PAINT RELATED MATERIAL

IATA-Shipping Name: PAINT or PAINT RELATED MATERIAL

IMDG-Shipping Name: PAINT or PAINT RELATED MATERIAL

14.3 Transport hazard class(es):

ADR-Class: 3

Safety Data Sheet

TIDILACK BIANCO

ADR-HI number: 30
IATA-Class: 3
IATA-Label: Flamm. Liquid
IMDG-Class: 3
Sea (IMO): -

14.4 Packing Group:
ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III
14.5 Environmental hazards
IMDG-Marine pollutant: No
14.6 Special Precautions for User



ADR-S.P.: 640E
ADR-Tunnel Restriction Code: (D/E)
IATA-Passenger Aircraft: 309
IATA-Cargo Aircraft: 310
IATA-ERG: 3L

IMDG-EmS: F-E , S-E

IMDG-Storage category: A
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Environmental Pollutant:
No

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

UE(dir 2004/42/CE) Pronto all'Uso / Ready to use
Volatile Organic compounds - VOCs = 28.04 %
Volatile Organic compounds - VOCs = 392.49 g/l

Volatile CMR substances = 0.00 %
Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %
Organic Carbon - C = 0.19

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2 Chemical Safety Assessment
No

Safety Data Sheet

TIDILACK BIANCO

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

- R10 Flammable.
 - R11 Highly flammable.
 - R20 Harmful by inhalation.
 - R20/21 Harmful by inhalation and in contact with skin.
 - R36 Irritating to eyes.
 - R36/37 Irritating to eyes and respiratory system.
 - R38 Irritating to skin.
 - R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 - R63 Possible risk of harm to the unborn child
 - R65 Harmful: may cause lung damage if swallowed.
 - R66 Repeated exposure may cause skin dryness or cracking.
 - R67 Vapours may cause drowsiness and dizziness.
-
- H226 Flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H312 Harmful in contact with skin.
 - H332 Harmful if inhaled.
 - H336 May cause drowsiness or dizziness.
 - H225 Highly flammable liquid and vapour.
 - H319 Causes serious eye irritation.
 - H335 May cause respiratory irritation.
 - H361 Suspected of damaging fertility or the unborn child.
 - H304 May be fatal if swallowed and enters airways.
 - H373 May cause damage to organs through prolonged or repeated exposure.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- NIOSH - Registry of toxic effects of chemical substances (1983)
- I.N.R.S. - Fiche Toxicologique
- CCNL - Appendix 1 "TLV for 1989-90"

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.