

# APM ESL 5000 Self Leveling Epoxy

ASIA PAINT SINGAPORE

Chemwatch Hazard Alert Code: 2

Chemwatch: 5175-14  
Version No: 2.1.1.1  
Safety Data Sheet

Issue Date: 01/01/2025  
Print Date: 01/01/2025  
Initial Date: Not Available  
S.GHS.SGP.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | APM ESL 5000 Self Leveling Epoxy   |
| Synonyms                      | Not Available  |
| Proper shipping name          | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ diglycidyl ether resin, liquid) |
| Other means of identification | Not Available  |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Use according to manufacturer's directions.<br>Base or Part A of a 2 pack<br>,<br>epoxy coating system<br>Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. <b>Do not</b> return the mixed material to the original containers<br>Two-component high build solventless epoxy for floors requiring high mechanical strength against chemical attacks and abrasion. |
|--------------------------|---|

### Details of the supplier of the safety data sheet

|                         |                                |
|-------------------------|--------------------------------|
| Registered company name | ASIA PAINT SINGAPORE           |
| Address                 | 20 Tuas Ave 8 639235 Singapore |
| Telephone               | +65 65 463 955                 |
| Fax                     | +65 65 463 855                 |
| Website                 | www.asiapaintsingapore.com     |
| Email                   | sales@asiapaintsingapore.com   |

### Emergency telephone number

|                                   |               |
|-----------------------------------|---------------|
| Association / Organisation        | Not Available |
| Emergency telephone numbers       | Not Available |
| Other emergency telephone numbers | Not Available |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture


#### CHEMWATCH HAZARD RATINGS

|              | Min | Max |
|--------------|-----|-----|
| Flammability | 1   | 1   |
| Toxicity     | 0   | 0   |
| Body Contact | 2   | 2   |
| Reactivity   | 2   | 2   |
| Chronic      | 2   | 2   |

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

|                    |  |
|--------------------|--|
| GHS Classification | Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Skin Sensitizer Category 1, Chronic Aquatic Hazard Category 2 |
|--------------------|--|

### Label elements

|                    |   |
|--------------------|---|
| GHS label elements |  |
|--------------------|---|

|             |         |
|-------------|---------|
| SIGNAL WORD | WARNING |
|-------------|---------|

### Hazard statement(s)

## APM ESL 5000 Self Leveling Epoxy

|      |   |
|------|---|
| H315 | Causes skin irritation                          |
| H319 | Causes serious eye irritation                   |
| H317 | May cause an allergic skin reaction             |
| H411 | Toxic to aquatic life with long lasting effects |

### Precautionary statement(s) Prevention

|      |  |
|------|--|
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.                          |
| P273 | Avoid release to the environment.  |
| P272 | Contaminated work clothing should not be allowed out of the workplace.     |

### Precautionary statement(s) Response

|                |  |
|----------------|--|
| P302+P352      | IF ON SKIN: Wash with plenty of water and soap   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P391           | Collect spillage.  |

### Precautionary statement(s) Storage

### Precautionary statement(s) Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration |
|------|--|

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

See section below for composition of Mixtures

### Mixtures

| CAS No     | %[weight] | Name   |
|------------|-----------|--|
| 25068-38-6 | >60       | <u>bisphenol A/ diglycidyl ether resin, liquid</u> |

## SECTION 4 FIRST AID MEASURES

### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:<br/>Wash out immediately with fresh running water.<br/>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.<br/>Seek medical attention without delay; if pain persists or recurs seek medical attention.<br/>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</p> |
| <b>Skin Contact</b> | <p>If skin contact occurs:<br/>Immediately remove all contaminated clothing, including footwear.<br/>Flush skin and hair with running water (and soap if available).<br/>Seek medical attention in event of irritation.</p>  |
| <b>Inhalation</b>   | <p>If fumes, aerosols or combustion products are inhaled remove from contaminated area.<br/>Other measures are usually unnecessary.</p>  |
| <b>Ingestion</b>    | <p>Immediately give a glass of water.<br/>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</p>  |

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

|  |   |
|--|---|
|  | <ul style="list-style-type: none"> <li>▶ Foam.</li> <li>▶ Dry chemical powder.</li> <li>▶ BCF (where regulations permit).</li> <li>▶ Carbon dioxide.</li> <li>▶ Water spray or fog - Large fires only.</li> </ul> |
|--|---|

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

## APM ESL 5000 Self Leveling Epoxy

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <p>Alert Fire Brigade and tell them location and nature of hazard.<br/>Wear breathing apparatus plus protective gloves.<br/>Prevent, by any means available, spillage from entering drains or water courses.<br/>Use water delivered as a fine spray to control fire and cool adjacent area.<br/><b>DO NOT</b> approach containers suspected to be hot.<br/>Cool fire exposed containers with water spray from a protected location.<br/>If safe to do so, remove containers from path of fire.<br/>Equipment should be thoroughly decontaminated after use.</p> |
| <b>Fire/Explosion Hazard</b> | <p>Combustible.<br/>Slight fire hazard when exposed to heat or flame.<br/>Heating may cause expansion or decomposition leading to violent rupture of containers.<br/>On combustion, may emit toxic fumes of carbon monoxide (CO).<br/>May emit acrid smoke.<br/>Mists containing combustible materials may be explosive.<br/>Combustion products include: carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material</p>  |

### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <p>In the event of a spill of a reactive diluent, the focus is on containing the spill to prevent contamination of soil and surface or ground water.<br/>If irritating vapors are present, an approved air-purifying respirator with organic vapor canister is recommended for cleaning up spills and leaks.<br/>For small spills, reactive diluents should be absorbed with sand.<br/>Environmental hazard - contain spillage.<br/>Clean up all spills immediately.<br/>Avoid breathing vapours and contact with skin and eyes.<br/>Control personal contact with the substance, by using protective equipment.<br/>Contain and absorb spill with sand, earth, inert material or vermiculite.<br/>Wipe up.<br/>Place in a suitable, labelled container for waste disposal.</p>  |
| <b>Major Spills</b> | <p>Environmental hazard - contain spillage.<br/>Industrial spills or releases of reactive diluents are infrequent and generally contained. If a large spill does occur, the material should be captured, collected, and reprocessed or disposed of according to applicable governmental requirements.<br/>An approved air-purifying respirator with organic-vapor canister is recommended for emergency work.<br/>Moderate hazard.<br/>Clear area of personnel and move upwind.<br/>Alert Fire Brigade and tell them location and nature of hazard.<br/>Wear breathing apparatus plus protective gloves.<br/>Prevent, by any means available, spillage from entering drains or water course.<br/>No smoking, naked lights or ignition sources.<br/>Increase ventilation.<br/>Stop leak if safe to do so.<br/>Contain spill with sand, earth or vermiculite.<br/>Collect recoverable product into labelled containers for recycling.<br/>Absorb remaining product with sand, earth or vermiculite.<br/>Collect solid residues and seal in labelled drums for disposal.<br/>Wash area and prevent runoff into drains.<br/>If contamination of drains or waterways occurs, advise emergency services.</p> |
|                     | <p>Personal Protective Equipment advice is contained in Section 8 of the SDS.</p>  |

### SECTION 7 HANDLING AND STORAGE

#### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <p><b>DO NOT allow clothing wet with material to stay in contact with skin</b><br/>Avoid all personal contact, including inhalation.<br/>Wear protective clothing when risk of exposure occurs.<br/>Use in a well-ventilated area.<br/>Prevent concentration in hollows and sumps.<br/><b>DO NOT enter confined spaces until atmosphere has been checked.</b><br/>Avoid smoking, naked lights or ignition sources.<br/>Avoid contact with incompatible materials.<br/>When handling, <b>DO NOT eat, drink or smoke.</b><br/>Keep containers securely sealed when not in use.<br/>Avoid physical damage to containers.<br/>Always wash hands with soap and water after handling.<br/>Work clothes should be laundered separately.<br/>Use good occupational work practice.<br/>Observe manufacturer's storage and handling recommendations contained within this MSDS.<br/>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</p> |
| <b>Other information</b> | <p>Store in original containers.<br/>Keep containers securely sealed.<br/>Store in a cool, dry, well-ventilated area.<br/>Store away from incompatible materials and foodstuff containers.<br/>Protect containers against physical damage and check regularly for leaks.<br/>Observe manufacturer's storage and handling recommendations contained within this MSDS.</p>   |

#### Conditions for safe storage, including any incompatibilities

|                           |  |
|---------------------------|--|
| <b>Suitable container</b> | <ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> |
|---------------------------|--|

## APM ESL 5000 Self Leveling Epoxy

### Storage incompatibility

Reactive diluents are stable under recommended storage conditions, but can decompose at elevated temperatures. In some cases, decomposition can cause pressure build-up in closed systems.

- ▶ Avoid cross contamination between the two liquid parts of product (kit).
- ▶ If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.
- ▶ This excess heat may generate toxic vapour
- ▶ Avoid reaction with amines, mercaptans, strong acids and oxidising agents

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Not Available

#### EMERGENCY LIMITS

| Ingredient                                  | Material name           | TEEL-1               | TEEL-2                | TEEL-3                 |
|---|-------------------------|----------------------|-----------------------|------------------------|
| bisphenol A/ diglycidyl ether resin, liquid | Epoxy resin (EPON 1001) | 90 mg/m <sup>3</sup> | 990 mg/m <sup>3</sup> | 5900 mg/m <sup>3</sup> |
| bisphenol A/ diglycidyl ether resin, liquid | Epoxy resin (EPON 1007) | 90 mg/m <sup>3</sup> | 990 mg/m <sup>3</sup> | 5900 mg/m <sup>3</sup> |
| bisphenol A/ diglycidyl ether resin, liquid | Epoxy resin (EPON 820)  | 41 mg/m <sup>3</sup> | 450 mg/m <sup>3</sup> | 2700 mg/m <sup>3</sup> |
| bisphenol A/ diglycidyl ether resin, liquid | Epoxy resin ERL-2795    | 32 mg/m <sup>3</sup> | 350 mg/m <sup>3</sup> | 2100 mg/m <sup>3</sup> |

| Ingredient                                  | Original IDLH | Revised IDLH  |
|---|---------------|---------------|
| bisphenol A/ diglycidyl ether resin, liquid | Not Available | Not Available |

### Exposure controls

| <b>Appropriate engineering controls</b>  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> |                             |   |  |  |   |                                  |  |   |  |                              |
|--|---|-----------------------------|---|--|--|---|----------------------------------|--|---|--|------------------------------|
|  | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table>  | Type of Contaminant:        | Air Speed:  | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min)                                | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)       | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.)                | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |
|  | Type of Contaminant:  | Air Speed:                  |   |  |  |   |                                  |  |   |  |                              |
|  | solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min) |   |  |  |   |                                  |  |   |  |                              |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)  | 0.5-1 m/s (100-200 f/min.)  |                             |   |  |  |   |                                  |  |   |  |                              |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)   | 1-2.5 m/s (200-500 f/min.)  |                             |   |  |  |   |                                  |  |   |  |                              |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).   | 2.5-10 m/s (500-2000 f/min.)  |                             |   |  |  |   |                                  |  |   |  |                              |
| <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table>  | Lower end of the range  | Upper end of the range      | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents  | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity  | 3: Intermittent, low production. | 3: High production, heavy use  | 4: Large hood or large air mass in motion | 4: Small hood-local control only   |                              |
| Lower end of the range   | Upper end of the range  |                             |   |  |  |   |                                  |  |   |  |                              |
| 1: Room air currents minimal or favourable to capture  | 1: Disturbing room air currents   |                             |   |  |  |   |                                  |  |   |  |                              |
| 2: Contaminants of low toxicity or of nuisance value only.   | 2: Contaminants of high toxicity  |                             |   |  |  |   |                                  |  |   |  |                              |
| 3: Intermittent, low production.   | 3: High production, heavy use   |                             |   |  |  |   |                                  |  |   |  |                              |
| 4: Large hood or large air mass in motion  | 4: Small hood-local control only  |                             |   |  |  |   |                                  |  |   |  |                              |
| <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> |   |                             |   |  |  |   |                                  |  |   |  |                              |

### Personal protection



## APM ESL 5000 Self Leveling Epoxy

|                                |  |
|--------------------------------|--|
| <b>Eye and face protection</b> | Safety glasses with side shields.<br>Chemical goggles.<br>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]  |
| <b>Skin protection</b>         | See Hand protection below  |
| <b>Hands/feet protection</b>   | <p><b>NOTE:</b></p> <p>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</p> <p>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</p> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>frequency and duration of contact,</li> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <p>When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</p> <p>When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</p> <p>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</p> <p>Contaminated gloves should be replaced.</p> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butadiene rubber), boots and aprons.</p> <p><b>DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).</b><br/><b>DO NOT use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.</b></p> |
| <b>Body protection</b>         | See Other protection below   |
| <b>Other protection</b>        | Overalls.<br>P.V.C. apron.<br>Barrier cream.<br>Skin cleansing cream.<br>Eye wash unit.  |
| <b>Thermal hazards</b>         | Not Available  |

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index"**.

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

APM ESL 5000 Self Leveling Epoxy Not Available

| Material | CPI |
|----------|-----|
|          |     |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator  |
|------------------------------------|----------------------|----------------------|-------------------------|
| up to 10 x ES                      | A-AUS P2             | -                    | A-PAPR-AUS / Class 1 P2 |
| up to 50 x ES                      | -                    | A-AUS / Class 1 P2   | -                       |
| up to 100 x ES                     | -                    | A-2 P2               | A-PAPR-2 P2 ^           |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|                        |  |  |               |
|------------------------|--|--|---------------|
| <b>Appearance</b>      | Clear or coloured liquid; does not mix with water. |  |               |
| <b>Physical state</b>  | Liquid   | <b>Relative density (Water = 1)</b>            | 1.12-1.39     |
| <b>Odour</b>           | Not Available                                      | <b>Partition coefficient n-octanol / water</b> | Not Available |
| <b>Odour threshold</b> | Not Available                                      | <b>Auto-ignition temperature (°C)</b>          | >300          |

Continued...

## APM ESL 5000 Self Leveling Epoxy

|   |                |   |                           |
|---|----------------|---|---------------------------|
| <b>pH (as supplied)</b>                             | Not Applicable | <b>Decomposition temperature</b>        | Not Available             |
| <b>Melting point / freezing point (°C)</b>          | Not Available  | <b>Viscosity (cSt)</b>                  | >140 KU, depend on colour |
| <b>Initial boiling point and boiling range (°C)</b> | >200           | <b>Molecular weight (g/mol)</b>         | Not Applicable            |
| <b>Flash point (°C)</b>                             | >150           | <b>Taste</b>                            | Not Available             |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>             | Not Available             |
| <b>Flammability</b>                                 | Not Applicable | <b>Oxidising properties</b>             | Not Available             |
| <b>Upper Explosive Limit (%)</b>                    | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b> | Not Available             |
| <b>Lower Explosive Limit (%)</b>                    | Not Available  | <b>Volatile Component (%vol)</b>        | <1                        |
| <b>Vapour pressure (kPa)</b>                        | Negligible     | <b>Gas group</b>                        | Not Available             |
| <b>Solubility in water (g/L)</b>                    | Immiscible     | <b>pH as a solution (1%)</b>            | Not Applicable            |
| <b>Vapour density (Air = 1)</b>                     | Not Available  | <b>VOC g/L</b>                          | Not Available             |

## SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | Unstable in the presence of incompatible materials.<br>Product is considered stable.<br>Hazardous polymerisation will not occur. |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | In animal testing, exposure to aerosols of some reactive diluents (notably o-cresol glycidyl ether, CAS RN: 2210-79-9) has been reported to affect the adrenal gland, central nervous system, kidney, liver, ovaries, spleen, testes, thymus, and respiratory tract.<br>Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.   |
| <b>Ingestion</b>    | Reactive diluents exhibit a range of ingestion hazards. Small amounts swallowed incidental to normal handling operations are not likely to cause injury. However, swallowing larger amounts may cause injury.<br>Male rats exposed to a single oral dose of bisphenol A diglycidyl ether (BADGE) at 750, 1000, and 2000 mg/kg/day showed a significantly increase in the number of immature and maturing sperm on the testis. There were no significant differences with respect to sperm head count, sperm motility, and sperm abnormality in the BADGE treatment groups<br>Ingestion may result in nausea, abdominal irritation, pain and vomiting   |
| <b>Skin Contact</b> | This material can cause inflammation of the skin on contact in some persons.<br>The material may accentuate any pre-existing dermatitis condition<br>Bisphenol A diglycidyl ether (BADGE) may produce contact dermatitis characterised by erythema and oedema, with weeping followed by crusting and scaling. A liquid resin with a molecular weight of 350 produced severe skin irritation in rabbits when applied daily for 4 hours over 20 days.<br>Following the initial contact there may be a discrete erythematous lesion, confined to the point of contact, which may persist for 48 hours to 10 days; the erythema may give way to a papular, vesicular rash with scaling.<br>In animals uncured resin produces moderate ante-mortem depression, loss of body weight and diarrhoea. Local irritation, inflammation and death resulting from respiratory system depression are recorded. Higher molecular weight resins generally produce lower toxicity.<br>Skin contact with reactive diluents may cause slight to moderate irritation with local redness. Repeated or prolonged skin contact may cause burns.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.   |
| <b>Eye</b>          | This material can cause eye irritation and damage in some persons.<br>Eye contact with reactive diluents may cause slight to severe irritation with the possibility of chemical burns or moderate to severe corneal injury.  |
| <b>Chronic</b>      | Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.<br>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.<br>There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.<br>Bisphenol A diglycidyl ethers (BADGEs) produce sensitisation dermatitis characterised by a papular, vesicular eczema with considerable itching of the back of the hand, the forearm and face and neck. This lesion may persist for 10-14 days after withdrawal from exposure and recur immediately on re-exposure. This dermatitis may persist for longer periods following each exposure but is unlikely to become more intense. Lesions may develop a brownish colour and scaling occurs frequently. Lower molecular weight species produce sensitisation more readily.<br>In mice technical grades of bisphenol A diglycidyl ether produced epidermal tumours and a small increase in the incidence kidney tumours in males and of lymphoreticular/ haematopoietic tumours in females. Subcutaneous injection produced a small number of fibrosarcomas in rats.<br>For some reactive diluents, prolonged or repeated skin contact may result in absorption of potentially harmful amounts or allergic skin reactions<br>Exposure to some reactive diluents (notably neopentylglycol diglycidyl ether, CAS RN:17557-23-2) has caused cancer in some animal testing.<br>Glycidyl ethers can cause genetic damage and cancer. |

|  |                 |                   |
|--|-----------------|-------------------|
| <b>APM ESL 5000 Self Leveling Epoxy</b>            | <b>TOXICITY</b> | <b>IRRITATION</b> |
|  | Not Available   | Not Available     |
| <b>bisphenol A/ diglycidyl ether resin, liquid</b> | <b>TOXICITY</b> | <b>IRRITATION</b> |
|  |                 |                   |

## APM ESL 5000 Self Leveling Epoxy

|   |                            |
|---|----------------------------|
| Dermal (rabbit) LD50: 6000 mg/kg <sup>[2]</sup> | Eye (rabbit): 100mg - Mild |
| dermal (rat) LD50: >800 mg/kg <sup>[1]</sup>    |                            |
| Oral (rat) LD50: >2400 mg/kg <sup>[2]</sup>     |                            |
| Oral (rat) LD50: 13447 mg/kg <sup>[1]</sup>     |                            |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

**BISPHENOL A/  
DIGLYCIDYL ETHER  
RESIN, LIQUID**

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics

Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner. However, BPA and several other derivatives did not show such activity. Results suggest that the 4-hydroxyl group of the A-phenyl ring and the B-phenyl ring of BPA derivatives are required for these hormonal activities, and substituents at the 3,5-positions of the phenyl rings and the bridging alkyl moiety markedly influence the activities.

Bisphenols promoted cell proliferation and increased the synthesis and secretion of cell type-specific proteins. When ranked by proliferative potency, the longer the alkyl substituent at the bridging carbon, the lower the concentration needed for maximal cell yield; the most active compound contained two propyl chains at the bridging carbon. Bisphenols with two hydroxyl groups in the para position and an angular configuration are suitable for appropriate hydrogen bonding to the acceptor site of the oestrogen receptor.

The substance is classified by IARC as Group 3:  
**NOT** classifiable as to its carcinogenicity to humans.  
Evidence of carcinogenicity may be inadequate or limited in animal testing.

In mice, dermal application of bisphenol A diglycidyl ether (BADGE) (1, 10, or 100 mg/kg) for 13 weeks produced mild to moderate chronic active dermatitis. At the high dose, spongiosis and epidermal micro abscess formation were observed. In rats, dermal application of BADGE (10, 100, or 1000 mg/kg) for 13 weeks resulted in a decrease in body weight at the high dose. The no-observable effect level (NOEL) for dermal exposure was 100 mg/kg for both sexes. In a separate study, application of BADGE (same doses) five times per week for ~13 weeks not only caused a decrease in body weight but also produced chronic dermatitis at all dose levels in males and at >100 mg/kg in females (as well as in a satellite group of females given 1000 mg/kg).

**Reproductive and Developmental Toxicity:** BADGE (50, 540, or 750 mg/kg) administered to rats via gavage for 14 weeks (P1) or 12 weeks (P2) produced decreased body weight in all males at the mid dose and in both males and females at the high dose, but had no reproductive effects. The NOEL for reproductive effects was 750 mg/kg.

**Carcinogenicity:** IARC concluded that "there is limited evidence for the carcinogenicity of bisphenol A diglycidyl ether in experimental animals." Its overall evaluation was "Bisphenol A diglycidyl ether is not classifiable as to its carcinogenicity to humans (Group 3). In a lifetime tumourigenicity study in which 90-day-old C3H mice received three dermal applications per week of BADGE (undiluted dose) for 23 months, only one out of 32 animals developed a papilloma after 16 months. A retest, in which skin paintings were done for 27 months, however, produced no tumours (Weil et al., 1963). In another lifetime skin-painting study, BADGE (dose n.p.) was also reported to be noncarcinogenic to the skin of C3H mice; it was, however, weakly carcinogenic to the skin of C57BL/6 mice (Holland et al., 1979; cited by Canter et al., 1986). In a two-year bioassay, female Fisher 344 rats dermally exposed to BADGE (1, 100, or 1000 mg/kg) showed no evidence of dermal carcinogenicity but did have low incidences of tumours in the oral cavity (U.S. EPA, 1997).

**Genotoxicity:** In *S. typhimurium* strains TA100 and TA1535, BADGE (10-10,000 ug/plate) was mutagenic with and without S9; negative results were obtained in TA98 and TA1537 (Canter et al., 1986; Pullin, 1977). In a spot test, BADGE (0.05 or 10.00 mg) failed to show mutagenicity in strains TA98 and TA100 (Wade et al., 1979). Negative results were also obtained in the body fluid test using urine of female BDF and ICR mice (1000 mg/kg BADGE), the mouse host-mediated assay (1000 mg/kg), micronucleus test (1000 mg/kg), and dominant lethal assay (~3000 mg/kg).

**Immunotoxicity:** Intracutaneous injection of diluted BADGE (0.1 mL) three times per week on alternate days (total of 8 injections) followed by a three-week incubation period and a challenge dose produced sensitisation in 19 of 20 guinea pigs

-

**Consumer exposure** to BADGE is almost exclusively from migration of BADGE from can coatings into food. Using a worst-case scenario that assumes BADGE migrates at the same level into all types of food, the estimated per capita daily intake for a 60-kg individual is approximately 0.16 ug/kg body weight/day. A review of one- and two-generation reproduction studies and developmental investigations found no evidence of reproductive or endocrine toxicity, the upper ranges of dosing being determined by maternal toxicity. The lack of endocrine toxicity in the reproductive and developmental toxicological tests is supported by negative results from both in vivo and in vitro assays designed specifically to detect oestrogenic and androgenic properties of BADGE. An examination of data from sub-chronic and chronic toxicological studies support a NOAEL of 50 mg/kg body weight/day from the 90-day study, and a NOAEL of 15 mg/kg body weight/day (male rats) from the 2-year carcinogenicity study. Both NOAELs are considered appropriate for risk assessment. Comparing the estimated daily human intake of 0.16 ug/kg body weight/day with the NOAELs of 50 and 15 mg/kg body weight/day shows human exposure to BADGE from can coatings is between 250,000 and 100,000-fold lower than the NOAELs from the most sensitive toxicology tests. These large margins of safety together with lack of reproductive, developmental, endocrine and carcinogenic effects supports the continued use of BADGE for use in articles intended to come into contact with foodstuffs.

Foetotoxicity has been observed in animal studies Oral (rabbit, female) NOEL 180 mg/kg (teratogenicity); NOEL (maternal 60 mg/kg

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ☹ | Carcinogenicity          | ☹ |
| Skin Irritation/Corrosion         | ✔ | Reproductivity           | ☹ |
| Serious Eye Damage/Irritation     | ✔ | STOT - Single Exposure   | ☹ |
| Respiratory or Skin sensitisation | ✔ | STOT - Repeated Exposure | ☹ |
| Mutagenicity                      | ☹ | Aspiration Hazard        | ☹ |

**Legend:** ✔ – Data required to make classification available  
✘ – Data available but does not fill the criteria for classification  
☹ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

Continued...

## APM ESL 5000 Self Leveling Epoxy

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Reactive diluents generally have a low to moderate potential for bioconcentration (tendency to accumulate in the food chain) and a high to very high potential for mobility in soil. Small amounts that escape to the atmosphere will photodegrade.

They would not be expected to persist in the environment.

Most reactive diluents should be considered slightly to moderately toxic to aquatic organisms on an acute basis while some might also be considered harmful to the environment.

Reactive diluents which are only slightly soluble in water and do not evaporate quickly are expected to sink to the bottom or float to the top, depending on the density, where they would be expected to biodegrade slowly.

**DO NOT** discharge into sewer or waterways.

### Persistence and degradability

| Ingredient                                  | Persistence: Water/Soil | Persistence: Air |
|---|-------------------------|------------------|
| bisphenol A/ diglycidyl ether resin, liquid | HIGH                    | HIGH             |

### Bioaccumulative potential

| Ingredient                                  | Bioaccumulation       |
|---|-----------------------|
| bisphenol A/ diglycidyl ether resin, liquid | LOW (LogKOW = 2.6835) |

### Mobility in soil

| Ingredient                                  | Mobility          |
|---|-------------------|
| bisphenol A/ diglycidyl ether resin, liquid | LOW (KOC = 51.43) |



## SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

|                              |  |
|------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and MSDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul> |
|------------------------------|--|

## SECTION 14 TRANSPORT INFORMATION

### Labels Required

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant |  |

### Land transport (UN)

|                         |  |
|-------------------------|--|
| UN number               | 3082   |
| Packing group           | III  |
| UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ diglycidyl ether resin, liquid) |
| Environmental hazard    | No relevant data   |



APM ESL 5000 Self Leveling Epoxy

|                                     |                    |                 |
|-------------------------------------|--------------------|-----------------|
| <b>Transport hazard class(es)</b>   | Class              | 9               |
|                                     | Subrisk            | Not Applicable  |
| <b>Special precautions for user</b> | Special provisions | 274;331;335;375 |
|                                     | Limited quantity   | 5 L             |

**Air transport (ICAO-IATA / DGR)**

|                                     |  |                |
|-------------------------------------|--|----------------|
| <b>UN number</b>                    | 3082   |                |
| <b>Packing group</b>                | III  |                |
| <b>UN proper shipping name</b>      | Environmentally hazardous substance, liquid, n.o.s. * (contains bisphenol A/ diglycidyl ether resin, liquid) |                |
| <b>Environmental hazard</b>         | No relevant data   |                |
| <b>Transport hazard class(es)</b>   | ICAO/IATA Class  | 9              |
|                                     | ICAO / IATA Subrisk  | Not Applicable |
|                                     | ERG Code   | 9L             |
| <b>Special precautions for user</b> | Special provisions   | A97 A158 A197  |
|                                     | Cargo Only Packing Instructions  | 964            |
|                                     | Cargo Only Maximum Qty / Pack  | 450 L          |
|                                     | Passenger and Cargo Packing Instructions   | 964            |
|                                     | Passenger and Cargo Maximum Qty / Pack   | 450 L          |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions  | Y964           |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack   | 30 kg G        |

**Sea transport (IMDG-Code / GGVSee)**

|                                     |  |                |
|-------------------------------------|--|----------------|
| <b>UN number</b>                    | 3082   |                |
| <b>Packing group</b>                | III  |                |
| <b>UN proper shipping name</b>      | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A/ diglycidyl ether resin, liquid) |                |
| <b>Environmental hazard</b>         | Not Applicable   |                |
| <b>Transport hazard class(es)</b>   | IMDG Class   | 9              |
|                                     | IMDG Subrisk   | Not Applicable |
| <b>Special precautions for user</b> | EMS Number   | F-A , S-F      |
|                                     | Special provisions   | 274 335        |
|                                     | Limited Quantities   | 5 L            |

**SECTION 15 REGULATORY INFORMATION**

**Safety, health and environmental regulations / legislation specific for the substance or mixture**

BISPHENOL A/ DIGLYCIDYL ETHER RESIN, LIQUID(25068-38-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

| National Inventory            | Status  |
|-------------------------------|---|
| Australia - AICS              | Y   |
| Canada - DSL                  | Y   |
| Canada - NDSL                 | N (bisphenol A/ diglycidyl ether resin, liquid)   |
| China - IECSC                 | Y   |
| Europe - EINEC / ELINCS / NLP | Y   |
| Japan - ENCS                  | Y   |
| Korea - KECI                  | Y   |
| New Zealand - NZIoC           | Y   |
| Philippines - PICCS           | Y   |
| USA - TSCA                    | Y   |
| <b>Legend:</b>                | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

**SECTION 16 OTHER INFORMATION**

**Other information**

**Ingredients with multiple cas numbers**

| Name  | CAS No                 |
|---|------------------------|
| bisphenol A/ diglycidyl ether resin, liquid | 25068-38-6, 25085-99-8 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.