

Product Description

Aerosol spray paint based on Acrylic resin

Recommended Use

Suitable for finishing or touching up of wood, metal, or objects which requires a fine finish

Features

Good applicability
Excellent adhesion
Good weathering
Non yellowing

Physical Characteristics

| Recommended Application Data | Dry Film Thickness (μm) | Theoretical Coverage (m ² /l) |
|------------------------------|--|--|
| | 10 – 30 μm | Depends on surface and thickness |
| Specific Gravity | 0.82 ± 0.02 | |
| Flash Point | -41 °C | |
| Finish | High Gloss, Semi-Gloss, Matt | |
| Color Range | Refer to Color Card. Other colors available upon request | |
| Standard Packing Size | 400 c.c. | |
| Shelf Life | 12 months | |

Application Method

| | |
|----------------|---|
| Spray Can | To apply an even coat, sweep the can horizontally and vertically past the object as you spray |
| Thinning Ratio | Not Applicable |

Drying Time At 30°C

| Touch Dry | Hard Dry | Overcoating Interval | |
|------------|----------|----------------------|----------------|
| | | Minimum | Maximum |
| 20 minutes | 2 hour | 3 hours | Not applicable |

Useful Information

| | |
|----------|--|
| Thinner | Not Applicable |
| Cleaner | Suitable commercial lacquer thinner |
| Storage | Store in a cool shaded dry area |
| Disposal | Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate Environmental Quality Regulations. |
| Other | Ozone friendly DME gas is used as propellant |

Surface Preparation

The service and life span and the service performance of paints are directly related to the degree of surface preparation.
 The surface to be overcoated must be dry and free from surface contaminants.
 Remove all oil, wax and grease by solvent cleaning.
 Remove all soluble salts by washing with fresh water.
 Remove all dirt and dust by dry brushing.
 Remove all loose flaking coatings, rust and mill scale by sanding / grinding, chipping, needle gun or spot blasting.

Coating Specifications

| | | | |
|-----------------------|--|--|--|
| 1 st Coat | | | |
| LUCKU Aerosol Acrylic | | | |

Notes

The coating specifications provided above are typical. For specific recommendations to suit individual applications, please refer to your Asia Paint Representative.
 Shake the product well before use.
 Contents under pressure. Not recommended for air freight.

Safety Precaution

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.
 Do not use in poorly ventilated areas, do not breathe in vapor or spray mist.
 This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge.
 In case of fire, use carbon dioxide, normal foam or dry agent.
 Contents under pressure. Do not burn, puncture or compress.
 Empty the cans before disposal.

First Aid

| | |
|--|--|
| Eyes | Wash off in flowing water or shower |
| Skin | Flush with plenty of water |
| Inhalation | Remove to fresh air, loosen collar and keep patient rested |
| Ingestion | If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel |
| For further safety information, please refer to our Safety Data Sheet (SDS) | |

Disclaimer

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.